



TECHNICAL FEATURES

- ✓ Meet requirements of the 2020 NECB
- ✓ Accommodates glazing thicknesses from 25mm to 56mm, based on project requirements
- ✓ Allows for structural silicone application from either the exterior or interior
- ✓ Integration of operable vents tailored to your project

PRODUCT DESCRIPTION

The 65 mm mullion curtain wall system, with variable depths ranging from 89 mm to 245 mm, has been specifically designed for medium and large spans. The high performance STE-7000 series combines resistance to air and water infiltration, thermal efficiency, and aesthetic quality while offering four configuration options

This system meets all current industry norms and standards and also complies with enhanced energy efficiency requirements for vision areas.

Module assembly is carried out in the factory whenever possible, under optimal conditions, ensuring a rigid unit with complete resistance to air and water infiltration.

The STE-7000 curtain wall system meets the most stringent performance requirements and is suitable for commercial buildings ranging from single-storey to multi-storey applications.

The development of custom extrusions is always possible based on project requirements - please contact the Stekar team.

WARRANTY

This product is covered under Stekar Systems standard warranty, certifying that the work will be free from manufacturing and installation defects under normal use conditions.

MAINTENANCE

The curtain wall system must be cleaned once installation is complete using products and methods that will not compromise the surface treatment or performance of the system. Regular maintenance must also be performed annually using the same procedures.



PERFORMANCES – TEST REPORTS – DOUBLE GLAZING

STRUCTURAL RESISTANCE (DEFLECTION)	Maximum deflection of L/500 at 4,08 kPa	ASTM E330
STRUCTURAL RESISTANCE (PRESSURE)	Design pressure of 4 080 Pa at DP85	ASTM E330
WATER PENETRATION RESISTANCE	No water penetration at 1,5 kPa pressure	ASTM E331 ASTM E547
AIR INFILTRATION AND EXFILTRATION	$Q_{mean} \leq 0,02 \text{ L/sm}^2 @ 75 \text{ Pa}$ $Q_{mean} \leq 0,07 \text{ L/sm}^2 @ 300 \text{ Pa}$	ASTM E283
THERMAL TRANSMITTANCE (OVERALL U-VALUE)	$U \leq 1,63 \text{ W/m}^2\text{K}$; double glazing 25,4 mm with low-e coating $U \leq 1,38 \text{ W/m}^2\text{K}$; double glazing 25,4 mm with a low-e coating and a pyrolytic coating on surface #4	NFRC 100 for Glazed Wall Curtain Wall (GWCW) Systems
CONDENSATION RESISTANCE	CR = 68 (glazing) CR = 76 (frame)	CAN/CSA A440.2

PERFORMANCES – TEST REPORTS – TRIPLE GLAZING

STRUCTURAL RESISTANCE (DEFLECTION)	Maximum deflection of L/580 at 3,36 kPa	ASTM E330
STRUCTURAL RESISTANCE (PRESSURE)	Design pressure of 3 360 Pa at DP70	ASTM E330
WATER PENETRATION RESISTANCE	No water penetration at 1,5 kPa pressure	ASTM E331 ASTM E547
AIR INFILTRATION AND EXFILTRATION	$Q_{mean} \leq 0,04 \text{ L/sm}^2 @ 75 \text{ Pa}$ $Q_{mean} \leq 0,11 \text{ L/sm}^2 @ 300 \text{ Pa}$ $Q_{mean} \leq 0,17 \text{ L/sm}^2 @ 450 \text{ Pa}$	ASTM E283
THERMAL TRANSMITTANCE (OVERALL U-VALUE)	$U \leq 0,87 \text{ W/m}^2\text{K}$; thermos triple 44,8 mm with low-e coating in face #2 and #4 or equivalent	NFRC 100 for Glazed Wall Curtain Wall (GWCW) Systems
CONDENSATION RESISTANCE	$I_G = 77$ (glazing) $I_F = 79$ (frame)	CAN/CSA A440.2



Components and Raw Materials

- Aluminum profiles are alloy AA6063, temper T5 or T6, and must comply with ASTM B221.
- Silicone must be a high-performance, multi-component structural silicone (e.g., Dow Corning Dowsil 795 or Tremco Proglaze II).
- The system is available in Class I or Class II anodized finishes, as well as painted finishes according to project requirements (e.g., DURANAR, DURANAR XL, D2000, and others).
- Aluminum must always be separated from dissimilar metals or masonry using an inert material or a conforming dielectric coating.
- All structural anchoring devices must be protected and separated from the aluminum using a dielectric coating.
- Glazing setting blocks are made of flexible PVC with a Shore A hardness of 83–85, and are compatible with the silicone specified for the project. Dimensions may vary depending on project requirements.
- The thermal break consists of rigid PVC (Shore A hardness 90 $\pm$ 5) or semi-rigid PVC (Shore A hardness 80 $\pm$ 5), or a combination of both.
- Weather-seal gaskets are made of Santoprene (TPV) with a Shore A hardness of 60 $\pm$ 5.
- Steel profiles for anchors and reinforcement components are fabricated according to certified and sealed shop drawings from a qualified engineer, meeting the required performance criteria and complying with CAN/CSA-G40.20/G40.21.
- All rigid insulation consists of high-density extruded polystyrene boards.
- Aluminum curtain walls manufactured in Quebec. Compliant with CAN/CSA-ISO 14025 and ISO 21930 standards. EPD available.

Design Criteria

- The following maximum tolerances must be respected during panel fabrication:
 - Length: $\pm$ 1 mm up to 1,219 mm
 - Length: $\pm$ 2 mm up to 3,538 mm
 - Height: $\pm$ 1 mm up to 1,219 mm
 - Height: $\pm$ 2 mm up to 3,538 mm
 - Diagonal: maximum 3 mm
 - Bow: 0.2% of the length, maximum 5 mm
- For load-calculation charts, refer to the wind load calculation document provided by Stekar.

Installation Conditions

- Once welding is completed, all welded surfaces must be cleaned, and a protective primer must be applied evenly to each surface.
- When the gap is 25 mm or greater, a galvanized steel flashing is required to allow proper installation of a waterproofing membrane. For gaps less than 25 mm, an Ethafoam backer rod may be used as a support for membrane application.
- High-density extruded polystyrene insulation panels must be installed to ensure continuity of the building's insulation, aligned with the curtain-wall glazing plane.
- Thermal insulation must be provided and installed wherever components penetrate or interrupt the building's insulation layer.
- The air/vapour barrier system must be installed in a manner that ensures a continuous barrier throughout the assembly.
- All joints between the curtain wall framing assemblies and adjacent building elements must be sealed to ensure system watertightness and airtightness.

Limitations

Product	Limitations
Curtain wall serie 7000 Structural Silicone Glazing	Please contact Stekar team

- In general, very large openings can be achieved within the curtain-wall system.
- A change in glass thickness may be required depending on the structural needs of the project and the glass span. Larger openings may require thicker insulating glass units (IGUs).
- For larger openings, laminated glass, or for any additional information, please contact the Stekar team, who can assess your project requirements and assist you throughout the design and execution process.